

## 400W AC LED Flood Light

Parameters	
Product Model	NES-FL-400
Power	400W
Input Range	90-275 V
LED Luminous Efficacy	≥145 lm/W
Light Source	OSRAM/BRIDGELUX LED
Color Temperature	2700-6500 K
Total Power Consumption	400W±10%
Driver Efficiency	>85%
LED Beam Angel	120°
Net Weight*	8.38±0.1 kg
Light Dimensions*	545x463x80 mm
Features	Auto Shutdown & Auto Restart Open & Short Circuit Protection Over Voltage Protection

### Actual Luminaire



>0.97	>70	IP66	>50000 Hrs.	<10%	50±3% Hz
Power Factor	CRI	IP Level	Working life	THD	Power Frequency

### Others

<b>Surge Protection</b>	<b>Maximum Temperature of Heat Sink</b>	<b>Primary Thermal Management</b>
>6 KV (Internal)	65 °C	Single Piece MCPCB with Thermal Pads
<b>Recommended Height</b>	<b>Storage Temperature</b>	<b>Secondary Thermal Management</b>
20-40 Meter	35 °C	High Pressure Aluminum Die Cast

\* Subject to change without notification

**Applications:** High masts, Container berths, docks, ports, Airport aprons, flyovers & bridges, Railway marshalling yards, Security lighting, sport Lighting, shopping malls and building façade.